

Contents

Abstract (in Chinese)	i
Abstract	ii
Acknowledgements	iii
Contents	iv
Table Captions	vi
Figure Captions	vii
Chapter 1 Introduction	1
1.1 Recent Development of VCSELs	1
1.2 Advantages and Drawbacks of VCSELs	2
1.3 VCSELs Applications	4
Chapter 2 Fundamental Design Consideration of VCSELs	9
2.1 Typical Lateral Confinement Schemes of VCSELs	9
2.1.1 Air-Post Structures	9
2.1.2 Etched/Regrown Buried Heterostructures	10
2.1.3 Ion-Implanted Structures	11
2.1.4 Oxide-Confined Structures	12
2.2 Threshold Condition	12
2.2.1 VCSELs with Bulk Active Layer	12
2.2.2 VCSELs with Quantum-Well Active Layer	14
2.3 Design and Analysis of Distributed Bragg Reflector	17
2.3.1 Transfer Matrix Method	18
2.3.2 Simulation Results of DBRs Reflectivity	19
Chapter 3 Experiments	29

3.1	Fabrication Procedures	29
3.2	Measurement Setup	33
Chapter 4	Experimental Results and Discussion	40
4.1	The CW L-I-V Characteristics	40
4.1.1	The Dependence of VCSEL Performance on Device Size	41
4.1.2	Slope Efficiency and Wall-Plug Efficiency	42
4.2	Transverse Mode Behavior	43
4.2.1	Influence of Spatial Hole Burning (SHB) and Self-Focusing Effect on the Transverse Modes	43
4.2.2	Kink and Slope Efficiency in L-I Curve	45
4.3	Influence of Temperature on VCSEL Performance	46
4.3.1	Thermal Roll-Over Effect	46
4.3.2	Determination of Active Region Temperature	47
4.3.3	Influence of Temperature on Threshold Current and Output Power	48
Chapter 5	Conclusion	63
	References	65

Table Captions

Table 2.1	Material parameters used in the calculation of the room temperature threshold current density of GaAs/AlGaAs VCSELs.	27
Table 2.2	The parameters of our ion-implanted VCSEL structure.	28



Figure Captions

Chapter 1

- Figure 1.1** Schematic drawing of (a) an edge-emitting laser and (b) a VCSEL. 6
- Figure 1.2** Scheme of a parallel free-space interconnection using VCSEL array and photodetector array integrated with microlens array. 7
- Figure 1.3** (a) A WDM optical data link transmits over a multimode optical fiber; (b) scheme of a monolithically integrated multiple wavelengths VCSEL (transmitter) and a channel-matched wavelength-selective narrowband photodetector array (receiver). 8

Chapter 2

- Figure 2.1** Structures of (a) air-post, (b) etched/regrown, (c) ion-implanted, (d) oxide-confined VCSELs. 21
- Figure 2.2** Schematic diagram of VCSELs with uniform gain structure. 22
- Figure 2.3** Scheme of a MQW with a separate confinement heterostructure. 22
- Figure 2.4** Threshold current density J_{th} and threshold current I_{th} against the diameter of active region $2W$ for VCSELs. 23
- Figure 2.5** The dependence of threshold current density J_{th} on the number of quantum wells n_w with different values of reflectivity R . 23
- Figure 2.6** Wave vectors and their associated electric fields for the case of normal incidence on a single dielectric layer. 24
- Figure 2.7** The reflection spectra of (a) top 20.5 pairs DBR, and (b) bottom 30.5 pairs DBR. 25
- Figure 2.8** The reflection spectrum for 850 nm VCSEL with 20.5 pairs top-DBR and 30.5 pairs bottom-DBR. 26

Chapter 3

- Figure 3.1** The process procedures of the device with (a) SiO₂ deposition, (b) top and bottom metal evaporation, (c) ion implantation, and (d) bonding pad metal

	evaporation.	34
Figure 3.2	Top view sketch of the device.	38
Figure 3.3	Probe station measurement setup.	39
 Chapter 4		
Figure 4.1	Schematic diagram of typical L-I-V characteristics of a VCSEL.	50
Figure 4.2	The continuous wave I-V characteristics of the devices with different active region diameter.	50
Figure 4.3	The series resistance versus active region radius.	51
Figure 4.4	The continuous wave L-I characteristics of the devices with different active region diameter.	51
Figure 4.5	The threshold current density and threshold current versus the active region area.	52
Figure 4.6	Operating current range and maximum output power versus the active region area.	52
Figure 4.7	The spatial hole burning effect starts with (a) the initial gain above threshold, (b) the increasing intensity of light reduces the gain in the middle along with the injection current, and (c) the gain in the surroundings eventually above threshold and the high order mode starts to lase.	53
Figure 4.8	(a) The self-focusing effect, and (b) the kink of the L-I curve corresponding to the transverse mode formation.	54
Figure 4.9	The slope efficiency in relation to the kink in the L-I curve.	55
Figure 4.10	The emission spectra in the vicinity of the kink in L-I curve.	56
Figure 4.11	(a) The scheme of the alignment between the gain peak as well as the FP resonance mode, and (b) the thermal roll-over effect.	57
Figure 4.12	The electroluminescence spectrum of a 12 μm diameter VCSEL at constant current 10mA, as a function of temperature from 20°C to 80°C.	57
Figure 4.13	The electroluminescence spectrum of a 12 μm diameter VCSEL at various bias current values at the heat-sink temperature of 25°C.	58
Figure 4.14	The measured FP mode wavelengths at various bias current values.	58

- Figure 4.15** (a) The CW L-I-V characteristics of a 12 μm diameter VCSEL at a constant heat-sink temperature of 25°C, and (b) the corresponding active region temperature at various current. 59
- Figure 4.16** The L-I characteristics of a 12 μm diameter VCSEL under CW current operations for various heat-sink temperatures from 20°C to 90°C. 60
- Figure 4.17** (a) The variation of threshold current for various heat-sink temperatures, and (b) the operating current range and maximum output power, as functions of the heat-sink temperature. 61
- Figure 4.18** The slope efficiency, as functions of the heat-sink temperature. 62

