CONTENTS

ABSTRA	ACT(in	Chinese)	i
ABSTR	ACT(in	English)	ii
ACKNO	WLED	OGEMENTS	iv
CONTE	NTS		v
LIST O	F FIGU	RES	vii
Chapter	1 Intro	oduction	1
1.1	Moti	vation	1
1.2	Surv	ey of Related Studies	2
1.3	Over	view of Proposed Approach	4
1.4	Cont	ributions	6
1.5	Thes	is Organization	8
Chapter	-	em Configuration and Guidance Principles	
2.1	Intro	duction	9
2.2	Syste	em ConfigurationE.S.	10
	2.2.1	Hardware configuration	11
	2.2.2	Software configuration	15
2.3	Lear	ning Strategy Principle and Major Steps in Proposed Process	15
2.4	Hum	an Detection Principle and Major Steps in Proposed Process	20
2.5	Hum	an Following Principle and Major Steps in Proposed Process	22
2.6	Hum	an Interaction Principle and Major Steps in Proposed Process	23
Chapter	3 Cam	era Calibration for Distance Computation	25
3.1	Intro	duction	25
	3.1.1	Coordinate Systems	26
	3.1.2	Directional Angles of Camera	28
3.2	Revie	ew of Proposed Distance Computation Method	30
3.3	Adap	otation to Different People's Heights	33
	3.3.1	Using reference data information	33
	3.3.2	Changes of viewing distance	38
3.4	Area	Tracking	41
	3.4.1	Human clothes color extraction	41
	3.4.2	Deciding area centers by a shape circumscribing method	43
	3.4.3	Adjustment of Camera orientations for area monitoring	44
Chanter	4 Hum	an Detection Technique for Person Following	47

	4.1	Introduction2		
	4.2	Propo	osed Process of Human Detection	48
	4.3	Revie	ew of a Face Detection Method	49
	4.4	Adap	tation to Changes of Luminance	52
		4.4.1	A Skin Detection Model	52
		4.4.2	Curve fitting	58
		4.4.3	Human detection by a progressive method	62
Cha	pter	5 Hum	an Following Techniques by Indoor Autonomous Vehicle	67
	5.1	Introd	duction	67
	5.2	Propo	osed Process of Human Following	68
	5.3	Fast I	Human Turning at A Corner in A Narrow Path	70
		5.3.1	Adaptation to fast turning by crossroad points	71
		5.3.2	Recording direction of fast human disappearance by a vehic	ele arm
				73
Cha	pter	6 Hum	an Interaction Techniques for Indoor Person Following	80
	6.1	Introd	duction	80
	6.2	Huma	an Facing Direction Detection	82
		6.2.1	Finding aspect ratios of human bodies	
		6.2.2	Finding human face centers	85
		6.2.3	Experimental results	
		6.2.4	Application as a tour guide	90
	6.3	Huma	an Hand Movement Detection by Motion Analysis	93
		6.3.1	Motion detection by frame differencing	95
		6.3.2	Vehicle calling by combining the facing direction detection	method
				96
		6.3.3	Experimental results	97
		6.3.4	Application as a shopping cart	98
Cha	pter	7 Expe	rimental Results and Discussions	102
	7.1	Expe	rimental Environment	102
	7.2	Expe	rimental Results	103
	7.3	Discu	assions	110
Cha	pter	8 Conc	clusions and Suggestions for Future Works	112
	8.1	Conc	lusions	112
	8.2	Sugge	estions for Future Works	114
Ref	eren	res		116

LIST OF FIGURES

Figure 1.1 A flowchart of proposed system	7
Figure 2.1 Equipment connection situation in this study	11
Figure 2.2 The vehicle Pioneer3 used in this study. (a) A front view of the vehic	le. (b) A
side view of the vehicle.	12
Figure 2.3 The camera AXIS210 used in this study. (a) A front view of the camera	nera. (b)
A side view of the camera.	13
Figure 2.4 The light equipments used in this study. (a) Light stand with an EYE	bulb off
(b) Light stand with the EYE bulb on	14
Figure 2.5 Digital light meter	15
Figure 2.6 An illustration of the learning strategy process to get the reference d	lata16
Figure 2.7 An illustration of the learning strategy process for different people h	neights
	17
Figure 2.8 An illustration of the learning strategy process for a person making	a fast
turn.	18
Figure 2.9 An illustration of the learning strategy process for the person follow	ing
applicationEIS.	19
Figure 2.10 An illustration of the human detection process.	21
Figure 2.11 An illustration of the human following process	23
Figure 2.12 An illustration of the human interaction process	24
Figure 3.1 The coordinate systems used in this study. (a) The image coordinate	system.
(b) The global coordinate system (c) The vehicle coordinate system.	(d) The
spherical coordinate system.	28
Figure 3.2 The pan angle of the camera. (a) $0 \le \theta_c \le \pi$. (b) $0 \ge \theta_c \ge -\pi$	29
Figure 3.3 The tilt angle of the camera. (a) $0 \le \varphi_c \le \frac{\pi}{2}$. (b) $0 \ge \varphi_c \ge -\frac{\pi}{2}$	29
Figure 3.4 Coordinate systems used (a) Image coordinate system. (b) Spherical	1
coordinate system.	31
Figure 3.5 Image coordinates mapped into real world space	31
Figure 3.6 The illustration of the distance d between a person and the vehicle.	32
Figure 3.7 Te reference data information	35
Figure 3.8 Getting the reference data $D_{refl.}$ (a) Reference person standing in from	nt of the
vehicle. (b) The vehicle can see the whole clothes of the Reference J	person.
	35
Figure 3.9 (a) The distance D_{refl} for the reference person. (b) The new distance D_{refl}	D_{newI} for
an athan mana an	40

Figure 3.10 Extraction of human clothes region
Figure 3.11 Deciding the area center
Figure 3.12 (a) The person is too right to the vehicle. (b) The result of the adjustment.
Eigene 4.1 An illustration of the human datastica areass.
Figure 4.1 An illustration of the human detection process
Figure 4.2 The elliptic skin model.
Figure 4.3 An illustration of the positions of the equipment in the experiment54
Figure 4.4 Retrieved five skin parts in the face.
Figure 4.5 The results of the experiment of building a skin detection model
Figure 4.6 The distribution of results of C_b and C_r . 58 Figure 4.7 The results of line fitting of C_c . The intensity V is from (a)16, 80 (b) 81, 145
Figure 4.7 The results of line fitting of C _b . The intensity Y is from (a)16~80 (b) 81~145 (c)146~234
Figure 4.8 The results of line fitting of C_r . The intensity Y is from (a)16~64 (b) 65~159
(c)160~23462
Figure 4.9 The detection of human face by the progressive method. (a) The block size is
320×240. (b) Skin color region of (a). (c) The block size is 160×120. (d) Skin
color region of (c). (e) The block size is 80×60 and the face of the person is
detected successfully. (f) Skin color region of (e)65
Figure 4.10 The detection of human face by progressive method. (a) The block size is
320×240. (b) Skin color region of (a). (c) The block size is 160×120. (d) Skin
color region of (c). (e) The block size is 80×60 and detect the face of the
person. (f) Skin color region of (e). (g) The block size is 40×30 and the face
of the person is detected successfully. (h) Skin color region of (g)66
Figure 5.1 An illustration of the human following process
Figure 5.2 An illustration of the turning mode
Figure 5.3 An illustration of the crossroads points
Figure 5.4 Choosing the correct crossroad point for searching the followed person73
Figure 5.5The direction of the vehicle in the real world
Figure 5.6 The original direction of the vehicle
Figure 5.7 An illustration of turning the robotic arm (a) The person is too right to the
vehicle. (b) Adjust the degree of the arm75
Figure 5.8 Measure the side of the turning direction. (a) Right. (b) Left77
Figure 5.9 The direction of the vehicle (a) Case 1. (b) Right and left side of (a). (c) Case
2. (d) Right and left side of (c). (e) Case 3. (f) Right and left side of (e). (g)
Case 4. (h) Right and left side of (g). (i) Case 5. (j) Right and left side of (j)
Figure 5.10 Turn to the correct direction (a) Turn right with angle θ_y . (b) Turn left with angle θ_y .
79 AUDIE 17.

Figure 6.1 A flowchart of human interaction81
Figure 6.2 An illustration of detection of a person's facing direction
Figure 6.3 An illustration of the facing direction of the person. (a) Front. (b) Back. (c)
Left. (d) Right88
Figure 6.4 Some experimental results of facing direction detection. (a) Front. (b) Back
(c) Right. (d) Left90
Figure 6.5 The process as a tour guide
Figure 6.6 An illustration of area information
Figure 6.7 An illustration of the vehicle being used as a tour guide92
Figure 6.8 An illustration of detection of hand movement
Figure 6.9 An experimental result of human hand movement detection. (a) The
detection of the facing direction in input images. (b) The result of the motion
detection98
Figure 6.10 The process as a shopping cart. 99
Figure 6.11 The illustration of calling the vehicle as a shopping cart100
Figure 6.12 An experimental result of the vehicle being a cart in the library101
Figure 7.1 The illustration of the CV Lab in NCTU
Figure 7.2 The vehicle follows a person as a shopping cart
Figure 7.3 An interface of the experiment. The green box shows the image stream and
the blue box shows the input image at this moment. The yellow box shows
the difference image and the red box shows the output image105
Figure 7.4 An experimental result of face detection and extraction of the clothes. (a)
The output image with a detected face region and the extracted clothes
region by region growing. (b) The image of the extracted clothes105
Figure 7.5 An experimental result of the person turning fast at a corner. (a) The input
image. (b) The position of the vehicle106
Figure 7.6 The vehicle makes an introduction about these books. (a) The facing
direction of the person is back and the media introduction is off. (b)The
person is facing some books and the media introduction is on107
Figure 7.7 An experimental result of detecting the person waving her hand. (a) The
input image. (b) The result of motion detection
Figure 7.8 An illustration of the experimental process
Figure 7.9 An illustration of the learned data and the actual path of following a person
in an experiment110